



surface
care
solutions

Scheda di Cura e Manutenzione

Ceramica Senio S.r.l.

Scheda di Cura e Manutenzione

Elementi in Cotto



surface
care
solutions

Scheda di Cura e Manutenzione

Ceramica Senio S.r.l.

NOTE INIZIALI

La seguente scheda vuole fornire informazioni utili per un corretto trattamento delle superfici in Cotto di Ceramica Senio S.r.l.. Queste indicazioni hanno lo scopo di spiegare le modalità di utilizzo e di applicazione dei prodotti FILA e gli strumenti necessari per eseguire il trattamento.

Per mantenere la superficie in buone condizioni nel tempo, si consiglia quindi di procedere con questo protocollo:

- Pulizia iniziale con DETERDEK PRO diluito 1:5, un detergente acido che consente di rimuovere lo sporco superficiale derivante dall'installazione del supporto. Per facilitare la pulizia di fine cantiere, si invita a rimuovere quanto più stucco fresco in fase di posa, seguendo le indicazioni del produttore dello stucco.
- Dopo la posa e/o dopo alcuni anni dall'installazione, procedere all'applicazione di un protettivo idro - oleorepellente a effetto naturale denominato W68. Come alternativa, è possibile usare FOB XTREME, protettivo antimacchia base solvente. Ricordiamo che sui supporti in cotto è altresì possibile applicare protettivi che diano un effetto bagnato al materiale. In questo caso, usare come protettivo WET ECO.
- In caso di pavimenti interni trattati con W68 o con FOB XTREME, terminare il ciclo di trattamento applicando una cera di finitura a scelta tra MATT (effetto naturale), SATIN (effetto satinato), LONGLIFE (effetto lucido).
- Effettuare la manutenzione ordinaria con CLEANER PRO diluito 1:200 o CLEAN&SHINE.
- Per decerare il pavimento o per effettuare una manutenzione straordinaria, usare PS87 PRO diluito 1:5. Successivamente, valutare il livello protettivo e, se necessario, riapplicare il protettivo e/o la cera.

Si invita a fare riferimento sempre alle schede tecniche più aggiornate e di seguire le indicazioni in esse riportate



surface
care
solutions

Scheda di Cura e Manutenzione

Ceramica Senio S.r.l.

Pavimenti

LAVAGGIO INIZIALE

Per questa operazione si consiglia di utilizzare DETERDEK PRO.

Il prodotto va applicato dopo la posa delle piastrelle per rimuovere i residui superficiali. DETERDEK PRO è un detergente acido utilizzabile sia a pavimento che a rivestimento. Non usare il prodotto su elementi sensibili agli acidi. Testare sempre prima dell'uso.

Resa: Il prodotto, diluito 1:5, ha una resa fino a 30mq/l



Come usarlo

<p>Spazzare bene il pavimento.</p>	<p>Diluire DETERDEK PRO in rapporto 1:5</p>	<p>Distribuire la soluzione sul pavimento con monospazzola</p>	<p>Lasciare agire per 4-5 minuti e dopo lavorare l'area con spazzolone o monospazzola con disco idoneo</p>	<p>Raccogliere i residui con aspiraliquidi e risciacquare con acqua pulita.</p>	<p>Non calpestare prima che l'area sia asciutta.</p>

PROTEZIONE ANTIMACCHIA - Base Acqua

Per questa operazione si consiglia di utilizzare W68.

Applicare il prodotto dopo la posa del materiale quando le aree sono pulite e asciutte. Il protettivo riduce l'assorbimento di acqua e di agenti macchianti nel materiale, senza modificarne l'aspetto. Non protegge dagli acidi. Leggere sempre le schede tecniche prima dell'uso. In caso di aree interne, è possibile valutare l'uso di una cera di finitura (MATT, SATIN o CLASSIC) a chiusura del trattamento.

Resa: I prodotti hanno una resa fino a 10 m²/L.



Come usarlo

<p>Provvedere ad accurata pulizia della superficie.</p>	<p>A pavimento asciutto e pulito, applicare W68 in modo uniforme.</p>	<p>Entro 10 minuti rimuovere completamente o eventuale residuo.</p>	<p>Non calpestare prima che l'area sia asciutta (4ore). Non bagnare prima di 24 ore</p>

PROTEZIONE ANTIMACCHIA - Base Solvente

Per questa operazione si consiglia di utilizzare FOB XTREME.

Applicare il prodotto dopo la posa del materiale quando le aree sono pulite e asciutte. Il protettivo riduce l'assorbimento di acqua e di agenti macchianti nel materiale, senza modificarne l'aspetto. Non protegge dagli acidi. Leggere sempre le schede tecniche prima dell'uso. In caso di aree interne, è possibile valutare l'uso di una cera di finitura (MATT, SATIN o CLASSIC) a chiusura del trattamento.

Resa: I prodotti hanno una resa fino a 10 m²/L.

Come usarlo

<p>Provvedere ad accurata pulizia della superficie.</p>	<p>A pavimento asciutto e pulito, applicare FOB XTREME in modo uniforme.</p>	<p>Entro 10 minuti rimuovere completamente o eventuale residuo.</p>	<p>Non calpestare prima che l'area sia asciutta (8ore). Non bagnare prima di 24 ore</p>



FINITURA - Opzionale e solo per pavimenti interni

Per questa operazione si consiglia di utilizzare MATT, SATIN o LONGLIFE.

Applicare il prodotto dopo la stesura del protettivo antimacchia. La cera permette di facilitare la manutenzione del supporto e di modificarne la finitura, rendendo il materiale opaco (usando MATT), satinato (usando SATIN) o lucido (usando LONGLIFE). Non usare il prodotto in esterno o in luoghi soggetti al contatto diretto con l'acqua. Testare prima dell'uso.

Ogni 2 - 3 mesi riapplicare una mano leggera di prodotto.

Copertura: I prodotti hanno una resa fino a 40 m²/L.

Come usarlo

<p>Plavorare su support pulito e asciutto</p>	<p>Applicare una moderata quantità di CERA in modo uniforme sul materiale con vello</p>	<p>Attendere un'ora, quindi, se necessario applicare una seconda mano di prodotto.</p>	<p>A pavimento asciutto e pulito, in caso di CLASSIC, lucidare con lucidatrice o panno di lana</p>	<p>Non calpestare prima che l'area sia asciutta.</p>



MANUTENZIONE ORDINARIA

Per questa operazione, si consiglia di utilizzare CLEANER PRO diluito 1:200.

Il prodotto pulisce delicatamente ma efficacemente tutte le superfici senza danneggiarle. È il prodotto ideale per la manutenzione ordinaria delle superfici.

Resa: Il prodotto, diluito 1:200, ha una resa fino a 1500mq/l

Come usarlo



<p>STEP 1</p>	<p>STEP 2</p>	<p>STEP 3</p>	<p>STEP 4</p>	<p>STEP 5</p>
<p>Spazzare bene il pavimento.</p>	<p>Diluire CLEANER PRO 1:200, ovvero 25ml in 5L d'acqua.</p>	<p>Pulire 2-3 m² per volta usando un mop con il metodo S movement.</p>	<p>Risciacquare e strizzare il mop prima di lavare una nuova area. Se il pavimento è molto sporco, lavarlo per due volte.</p>	<p>Non camminare sulla superficie fino a quando non è completamente asciutta.</p>

MANUTENZIONE STRAORDINARIA

Per questa operazione, si consiglia di utilizzare CLEANER PRO.

Il prodotto rimuove lo sporco ostinato superficiale, ripristinando l'aspetto originale del pavimento. Si consiglia di procedere a questa pulizia quando se ne presenta la necessità. In caso di sporco ostinato utilizzare PS87 PRO diluito 1:10. Per decerare, usare PS87 PRO diluito 1:5.

Resa: Il prodotto, diluito 1:30, ha una resa fino a 50mq/l

Come usarlo



<p>STEP 1</p>	<p>STEP 2</p>	<p>STEP 3</p>	<p>STEP 4</p>	<p>STEP 5</p>	<p>STEP 6</p>
<p>Spazzare bene il pavimento.</p>	<p>Diluire CLEANER PRO in rapporto 1:30.</p>	<p>Distribuire la soluzione sul pavimento con monospazzola con disco bianco.</p>	<p>Lasciare agire per 4-5 minuti e dopo lavorare l'area con spazzolone o monospazzola con disco idoneo</p>	<p>Raccogliere i residui con aspiraliquidi e risciacquare con acqua pulita.</p>	<p>Non calpestare prima che l'area sia asciutta.</p>



surface
care
solutions

Scheda di Cura e Manutenzione

Ceramica Senio S.r.l.

Rivestimenti e Top



surface
care
solutions

Scheda di Cura e Manutenzione

Ceramica Senio S.r.l.

LAVAGGIO INIZIALE

Per questa operazione si consiglia di utilizzare DETERDEK PRO.

Il prodotto va applicato dopo la posa delle piastrelle per rimuovere i residui superficiali. DETERDEK PRO è un detergente acido utilizzabile sia a pavimento che a rivestimento. Per facilitare la pulizia di fine cantiere, rimuovere quanto più residui fresco di stucco in fase di posa. Non applicare su elementi sensibili agli acidi

Resa: Il prodotto, diluito 1:5, ha una resa fino a 30mq/l



Come usarlo

<p>Bagnare la superficie con acqua</p>	<p>Diluire DETERDEK PRO 1:5</p>	<p>Distribuire la soluzione con pennello o a spray</p>	<p>Lasciare agire per 5 minuti e dopo strofinare la superficie con una spugna scotch brite idonea</p>	<p>Raccogliere i residui e risciacquare con acqua pulita</p>

PROTEZIONE ANTIMACCHIA - Base Acqua

Per questa operazione si consiglia di utilizzare W68.

Applicare il prodotto dopo la posa del materiale quando le aree sono pulite e asciutte. Il protettivo riduce l'assorbimento di acqua e di agenti macchianti nel materiale, senza modificarne l'aspetto. Non protegge dagli acidi. Leggere sempre le schede tecniche prima dell'uso.

Come alternativa, per esterni o ambienti molto umidi, usare FOB XTREME.

Resa: I prodotti hanno una resa fino a 10 m²/L.



Come usarlo

<p>Provvedere ad un'accurata pulizia della superficie.</p>	<p>Su superficie asciutta e pulita, applicare con pennello in modo uniforme.</p>	<p>Attendere 10 minuti, quindi rimuovere ogni residuo non assorbito. Non si deve formare un film.</p>	<p>Non toccare prima di 4 ore e non bagnare prima di 24 ore</p>

PROTEZIONE ANTIMACCHIA - Base Solvente

Per questa operazione si consiglia di utilizzare FOB XTREME.

Applicare il prodotto dopo la posa del materiale quando le aree sono pulite e asciutte. Il protettivo riduce l'assorbimento di acqua e di agenti macchianti nel materiale, senza modificarne l'aspetto. Non protegge dagli acidi. Leggere sempre le schede tecniche prima dell'uso.

Resa: I prodotti hanno una resa fino a 10 m²/L.



Come usarlo



Provvedere ad un'accurata pulizia della superficie.



Su superficie asciutta e pulita, applicare con pennello in modo uniforme.



Attendere 10 minuti, quindi rimuovere ogni residuo non assorbito. Non si deve formare un film.




Non toccare prima di 8 ore e non bagnare prima di 24 ore

MANUTENZIONE ORDINARIA

Per questa operazione, si consiglia di utilizzare CLEAN&SHINE.

Il prodotto pulisce delicatamente ma efficacemente tutte le superfici senza danneggiarle. È il prodotto ideale per la manutenzione ordinaria delle superfici.

Come usarlo



Spruzzare il prodotto sulla superficie tenendo il flacone in posizione verticale a circa 20/30 cm dal punto di applicazione.



Passare l'area con panno morbido.





surface
care
solutions

Scheda di Cura e Manutenzione

Ceramica Senio S.r.l.

MANUTENZIONE STRAORDINARIA

Per questa operazione, si consiglia di utilizzare CLEANER PRO.

Il prodotto rimuove lo sporco ostinato superficiale, ripristinando l'aspetto originale del pavimento. Si consiglia di procedere a questa pulizia quando se ne presenta la necessità. In caso di sporco ostinato utilizzare PS87 PRO diluito 1:10. In caso di calcare, usare DETERDEK PRO diluito 1:5

Resa: Il prodotto, diluito 1:30, ha una resa fino a 50mq/l



Come usarlo

STEP 1	STEP 2	STEP 3	STEP 4	STEP 5
Bagnare la superficie con acqua.	Diluire CLEANER PRO in rapporto 1:30.	Distribuire la soluzione sulla parete con un pennello o con la pompa airless.	Lasciare agire per 4-5 minuti e dopo lavorare l'area con spugna Scotch Brite verde o spazzola di saggina manuale.	Raccogliere i residui e risciacquare con acqua pulita.

TABELLA MACCHIE

LAVAGGIO STRAORDINARIO	PS87 PRO
SILICONE	ZEROSIL
BEVANTE GASSATE	SR95
URINA O VOMITO	
CAFFE/VINO	
SANGUE	
INCHIOSTRO	
NICOTINA	
TINTE	
RUGGINE	NORUST
OLIO	NOSPOT

NOTE

Evitare l'uso di sostanze acide o alcaline, o di detersivi a base di solvente per la pulizia ordinaria. In caso di situazioni particolari, contattare FILA per valutare ulteriori soluzioni. Per qualsiasi richiesta di informazioni, scrivere a info@filasolutions.com.



surface
care
solutions

Care & Maintenance Sheet

Ceramica Senio S.r.l.

Care & Maintenance Sheet

Terracotta Surfaces



INITIAL NOTES

This document provides guidelines for the correct treatment of Ceramica Senio S.r.l. terracotta surfaces, describing the application of FILA products and the required tools.

To maintain the surfaces at their best, we suggest to follow the below steps:

TREATMENT PROTOCOL

- Initial cleaning

Clean the surface with DETERDEK PRO diluted 1:5 to remove installation residues. Remove fresh grout during installation according to the grout manufacturer's instructions.

- Protective treatment

After installation or over time, apply a water- and oil-repellent protector with natural effect (W68).

As an alternative, use FOB XTREME (solvent-based stain protector).

For a wet-look effect, apply WET ECO.

- Finishing (interior floors only)

For surfaces treated with W68 or FOB XTREME, apply a finishing wax: MATT (natural), SATIN (satin) or LONGLIFE (gloss)

- Routine maintenance

Clean with CLEANER PRO diluted 1:200 or CLEAN & SHINE.

- Extraordinary maintenance

For wax removal or deep cleaning, use PS87 PRO diluted 1:5, then reapply the protector and/or wax if necessary.

Please always refer to the latest technical data sheets and follow the instructions given therein.



surface
care
solutions

Care & Maintenance Sheet

Ceramica Senio S.r.l.

Floors



surface care solutions

Care & Maintenance Sheet

Ceramica Senio S.r.l.

INITIAL CLEANING

We recommend using DETERDEK PRO for this operation.

The product should be applied after the installation of the tiles to remove superficial residues. DETERDEK PRO is an acidic cleaner that can be used on both floor and wall tiles. Do not use of materials that are sensitive to acids. Remove as much fresh grout as possible during the grouting.

Coverage: when diluted 1:5, it covers up to 30mq/l



How to use it

<p>Sweep the floor well.</p>	<p>Dilute DETERDEK PRO 1:5</p>	<p>Distribute the solution with a floor scrubber fitted with a suitable pad.</p>	<p>Leave to act for 4-5 minutes and then wash the floor with a brush or floor scrubber fitted with a white pad.</p>	<p>Remove residue with a wet vacuum and rinse with clean water.</p>	<p>Do not walk on the surface until it is completely dry.</p>

WATER AND OIL REPELLENT PROTECTION – Water Based

W68 is recommended for this operation.

Apply the product on the installed and clean material. The sealer reduces the absorption of water and staining agents, without changing the superficial finishing. The product does not protect against acids. Always read the technical data sheets before use. As an alternative, for materials installed outside or in very humid environments, use FOB XTREME.

Coverage: It covers up to 10 mq/l



How to use it

<p>Be sure that the surface is clean and dry</p>	<p>Apply W68 E evenly on the material with a fleece pad or other appropriate applicator.</p>	<p>Massage the surface with a cloth or floor cleaning machine fitted with a white disc.</p>	<p>Within 10 minutes, completely remove any residue with a microfibre cloth.</p>	<p>Do not walk on the surface until it is completely dry.</p>



surface care solutions

Care & Maintenance Sheet

Ceramica Senio S.r.l.

WATER AND OIL REPELLENT PROTECTION – Solvent Based

FOB XTREME is recommended for this operation.

Apply the product on the installed and clean material. The sealer reduces the absorption of water and staining agents, without changing the superficial finishing. The product does not protect against acids. Always read the technical data sheets before use.

Coverage: It covers up to 10mq/l

How to use it

<p>Be sure that the surface is clean and dry</p>	<p>Apply FOB XTREME evenly on the material with a fleece pad or other appropriate applicator.</p>	<p>Massage the surface with a cloth or floor cleaning machine fitted with a white disc.</p>	<p>Within 10 minutes, completely remove any residue with a microfibre cloth.</p>	<p>Do not walk on the surface until it is completely dry.</p>



FINISHING – Optional; to be use only in case of internal floor

We recommend using MATT, SATIN or CLASSIC for this operation.

Apply the product after the stain protection has been applied. The wax makes it easier to maintain the substrate and modify the finish, making the material matt (using MATT), satin (using SATIN) or glossy (using CLASSIC). Do not use the product outdoors or in places subject to direct contact with water. Test before use.

Every 2 - 3 months reapply a light coat of product.

Coverage: It covers up to 40mq/l

How to use it

<p>When the floor is clean and dry, apply a moderate amount of WAX evenly with a fleece pad</p>	<p>Wait one hour and apply a second coat if necessary.</p>	<p>When the floor is clean and dry, when applying CLASSIC, polish the surface</p>	<p>Do not walk on the surface until it is completely dry.</p>





surface
care
solutions

Care & Maintenance Sheet

Ceramica Senio S.r.l.

ORDINARY MAINTENANCE



For this operation, we recommend using CLEANER PRO diluted 1:200.

The product gently but effectively cleans all surfaces without damaging them. It is the ideal product for routine maintenance of surfaces.

Coverage: The product, diluted 1:200, covers up to 1500mq/l



How to use it

<p>STEP 1</p> 	<p>STEP 2</p>  <p>25ml 5L</p>	<p>STEP 3</p>  <p>2 m² 1,5 m²</p>	<p>STEP 4</p> 	<p>STEP 5</p>  <p>X</p>
<p>Sweep the floor well.</p>	<p>Dilute CLEANER PRO 1:200</p>	<p>Clean 2-3 m² at a time with a mop following an S-shape pattern.</p>	<p>Rinse and wring the mop before washing a new area. If the floor is very dirty, wash it twice.</p>	<p>Do not walk on the surface until it is completely dry.</p>

EXTRAORDINARY MAINTENANCE


For this operation, we recommend CLEANER PRO.

The product removes stubborn dirt, restoring the floor's original appearance. It is recommended to carry out this cleaning when there is the need. In case of stubborn dirt, use PS87 PRO diluted 1:10. If you need to dewax the floor, use PS87 PRO diluted 1:5.

Coverage: The product, diluted 1:30, covers up to 50mq/l



How to use it

<p>STEP 1</p> 	<p>STEP 2</p>  <p>0,3L 5L</p>	<p>STEP 3</p>  <p>2 m² 1,5 m²</p>	<p>STEP 4</p> 	<p>STEP 5</p> 	<p>STEP 6</p>  <p>X</p>
<p>Sweep the floor well.</p>	<p>Dilute CLEANER PRO 1:30.</p>	<p>Distribute the solution with a floor scrubber fitted with a white pad.</p>	<p>Leave to act for 4-5 minutes and then wash the floor with a brush or floor scrubber fitted with a white pad.</p>	<p>Remove residue with a wet vacuum and rinse with clean water.</p>	<p>Do not walk on the surface until it is completely dry.</p>



surface
care
solutions

Care & Maintenance Sheet

Ceramica Senio S.r.l.

Walls & Tops



surface
care
solutions

Care & Maintenance Sheet

Ceramica Senio S.r.l.

INITIAL CLEANING

We recommend using DETERDEK PRO for this operation.

The product should be applied after the installation of the tiles to remove superficial residues. DETERDEK PRO is an acid cleaner that can be used on both floor and wall tiles. Do not use on materials that are sensitive to acids.

Coverage: when diluted 1:5, it covers up to 30mq/l



How to use it

<p>STEP 1</p>	<p>STEP 2</p>	<p>STEP 3</p>	<p>STEP 4</p>	<p>STEP 5</p>
<p>Wet the surface with water.</p>	<p>Dilute DETERDEK PRO 1:5</p>	<p>Distribute the solution on the surface with a brush or airless sprayer.</p>	<p>Let sit for 4-5 minutes, then clean the area with an abrasive Scotch Brite sponge or brush.</p>	<p>Remove residue and rinse with clean water.</p>

WATER AND OIL REPELLENT PROTECTION - Water Based

W68 is recommended for this operation.

Apply the product on the installed and clean material. The sealer reduces the absorption of water and staining agents, without changing the superficial finishing. The product does not protect against acids. Always read the technical data sheets before use. As an alternative, for materials installed outside or in very humid environments, use FOB XTREME.

Coverage: It covers up to 10mq/l



How to use it

<p>STEP 1</p>	<p>STEP 2</p>	<p>STEP 3</p>	<p>STEP 4</p>
<p>Clean the surface well.</p>	<p>On a clean and dry surface, apply the product evenly with a brush</p>	<p>Wait 10 minutes, then remove any unabsorbed residue. The product must not form a film.</p>	<p>Do not touch the surface within the first 4 hours and do not wet the surface for 24 hours.</p>



surface care solutions

Care & Maintenance Sheet

Ceramica Senio S.r.l.

WATER AND OIL REPELLENT PROTECTION – Solvent Based

FOB XTREME is recommended for this operation.

Apply the product on the installed and clean material. The sealer reduces the absorption of water and staining agents, without changing the superficial finishing. The product does not protect against acids. Always read the technical data sheets before use.

Coverage: It covers up to 10mq/l

How to use it



<p>STEP 1</p> 	<p>STEP 2</p> 	<p>STEP 3</p> 	<p>STEP 4</p> 
<p>Clean the surface well.</p>	<p>On a clean and dry surface, apply the product evenly with a brush</p>	<p>Wait 10 minutes, then remove any unabsorbed residue. The product must not form a film.</p>	<p>Do not touch the surface within the first 8 hours and do not wet the surface for 24 hours.</p>

ORDINARY MAINTENANCE

For this operation, we recommend using CLEAN&SHINE

The product gently but effectively cleans all surfaces without damaging them. It is the ideal product for routine maintenance of surfaces.

How to use it

<p>STEP 1</p> 	<p>STEP 2</p> 
<p>Spray the product on the surface keeping the bottle upright, 20-30 cm from the point of application.</p>	<p>Clean the area with a soft cloth.</p>





surface
care
solutions

Care & Maintenance Sheet

Ceramica Senio S.r.l.

EXTRAORDINARY MAINTENANCE

For this operation, we recommend CLEANER PRO.

The product removes stubborn dirt, restoring the floor's original appearance. It is recommended to carry out this cleaning when there is the need. In case of stubborn dirt, use PS87 PRO diluted 1:10. In case of limescale residues, use DETERDEK PRO diluted 1:5.

Coverage: The product, diluted 1:30, covers up to 50mq/l



How to use it

STEP 1	STEP 2	STEP 3	STEP 4	STEP 5
Wet the surface with water.	Dilute CLEANER PRO 1:30	Distribute the solution on the surface with a brush or airless sprayer.	Let sit for 4-5 minutes, then clean the area with an abrasive Scotch Brite sponge or brush.	Remove residue and rinse with clean water.



surface
care
solutions

Care & Maintenance Sheet

Ceramica Senio S.r.l.

STAIN CHART

OIL AND GREASE	NOSPOT
CARBONATED BEVERAGES AND JUICES	SR95
URINE AND VOMIT	
COFFEE AND WINE	
BLOOD	
INK / MARKER	
NICOTINE	
HAIR DYE	
SILICONE	
POLYURETHANE FOAM	
ADHESIVE TAPE RESIDUE	
RESIN	
RUSS	NORUSS

NOTE

Avoid the use of acidic or alkaline substances, or solvent-based cleaning agents for the ordinary maintenance.

In case of special situations, contact FILA to evaluate further solutions.

For any enquiries, please write to info@filasolutions.com.



surface
care
solutions

Care & Maintenance Sheet

Ceramica Senio S.r.l.

Care & Maintenance Sheet

Terracotta Surfaces



INITIAL NOTES

This document provides guidelines for the correct treatment of Ceramica Senio S.r.l. terracotta surfaces, describing the application of FILA products and the required tools.

To maintain the surfaces at their best, we suggest to follow the below steps:

TREATMENT PROTOCOL

- Initial cleaning

Clean the surface with DETERDEK diluted 1:5 to remove installation residues. Remove fresh grout during installation according to the grout manufacturer's instructions.

- Protective treatment

After installation or over time, apply a water- and oil-repellent protector with natural effect (MP90ECO PLUS).

As an alternative, use FOB (solvent-based stain protector).

For a wet-look effect, apply WET ECO.

- Finishing (interior floors only)

For surfaces treated with W68 or FOB, apply a finishing wax: MATT (natural), SATIN (satin) or LONGLIFE (gloss)

- Routine maintenance

Clean with CLEANALL diluted 1:200 or CLEANALL SPRAY.

- Extraordinary maintenance

For wax removal or deep cleaning, use PS87 diluted 1:5, then reapply the protector and/or wax if necessary.

Please always refer to the latest technical data sheets and follow the instructions given therein.



surface
care
solutions

Care & Maintenance Sheet

Ceramica Senio S.r.l.

Floors



surface care solutions

Care & Maintenance Sheet

Ceramica Senio S.r.l.

INITIAL CLEANING

We recommend using DETERDEK for this operation.

The product should be applied after the installation of the tiles to remove superficial residues. DETERDEK is an acidic cleaner that can be used on both floor and wall tiles. Do not use of materials that are sensitive to acids. Remove as much fresh grout as possible during the grouting.

Coverage: when diluted 1:5, it covers up to 30mq/l



How to use it

<p>Sweep the floor well.</p>	<p>Dilute DETERDEK 1:5</p>	<p>Distribute the solution with a floor scrubber fitted with a suitable pad.</p>	<p>Leave to act for 4-5 minutes and then wash the floor with a brush or floor scrubber fitted with a white pad.</p>	<p>Remove residue with a wet vacuum and rinse with clean water.</p>	<p>Do not walk on the surface until it is completely dry.</p>

WATER AND OIL REPELLENT PROTECTION – Water Based

MP90ECO PLUS is recommended for this operation.

Apply the product on the installed and clean material. The sealer reduces the absorption of water and staining agents, without changing the superficial finishing. The product does not protect against acids. Always read the technical data sheets before use. As an alternative, for materials installed outside or in very humid environments, use FOB.

Coverage: It covers up to 10 mq/l



How to use it

<p>Be sure that the surface is clean and dry</p>	<p>Apply MP90ECO PLUS evenly on the material with a fleece pad or other appropriate applicator.</p>	<p>Massage the surface with a cloth or floor cleaning machine fitted with a white disc.</p>	<p>Within 10 minutes, completely remove any residue with a microfibre cloth.</p>	<p>Do not walk on the surface until it is completely dry.</p>



surface care solutions

Care & Maintenance Sheet

Ceramica Senio S.r.l.

WATER AND OIL REPELLENT PROTECTION - Solvent Based

FOB is recommended for this operation.

Apply the product on the installed and clean material. The sealer reduces the absorption of water and staining agents, without changing the superficial finishing. The product does not protect against acids. Always read the technical data sheets before use.

Coverage: It covers up to 10mq/l

How to use it

<p>STEP 1</p> <p>Be sure that the surface is clean and dry</p>	<p>STEP 2</p> <p>Apply FOB evenly on the material with a fleece pad or other appropriate applicator.</p>	<p>STEP 3</p> <p>Massage the surface with a cloth or floor cleaning machine fitted with a white disc.</p>	<p>STEP 4</p> <p>Within 10 minutes, completely remove any residue with a microfibre cloth.</p>	<p>STEP 5</p> <p>Do not walk on the surface until it is completely dry.</p>
---	---	--	---	--



FINISHING - Optional; to be use only in case of internal floor

We recommend using MATT, SATIN or CLASSIC for this operation.

Apply the product after the stain protection has been applied. The wax makes it easier to maintain the substrate and modify the finish, making the material matt (using MATT), satin (using SATIN) or glossy (using CLASSIC). Do not use the product outdoors or in places subject to direct contact with water. Test before use.

Every 2 - 3 months reapply a light coat of product.

Coverage: It covers up to 40mq/l

How to use it

<p>STEP 2</p> <p>When the floor is clean and dry, apply a moderate amount of WAX evenly with a fleece pad</p>	<p>STEP 3</p> <p>Wait one hour and apply a second coat if necessary.</p>	<p>STEP 4</p> <p>When the floor is clean and dry, when applying CLASSIC, polish the surface</p>	<p>STEP 5</p> <p>Do not walk on the surface until it is completely dry.</p>
--	---	--	--





surface
care
solutions

Care & Maintenance Sheet

Ceramica Senio S.r.l.

ORDINARY MAINTENANCE

For this operation, we recommend using CLEANALL diluted 1:200.

The product gently but effectively cleans all surfaces without damaging them. It is the ideal product for routine maintenance of surfaces.

Coverage: The product, diluted 1:200, covers up to 1500mq/l

How to use it

STEP 1
Sweep the floor well.

STEP 2
Dilute CLEANALL 1:200

STEP 3
Clean 2-3 m² at a time with a mop following an S-shape pattern.

STEP 4
Rinse and wring the mop before washing a new area. If the floor is very dirty, wash it twice.

STEP 5
Do not walk on the surface until it is completely dry.



EXTRAORDINARY MAINTENANCE

For this operation, we recommend CLEANALL.

The product removes stubborn dirt, restoring the floor's original appearance. It is recommended to carry out this cleaning when there is the need. In case of stubborn dirt, use PS87 diluted 1:10. If you need to dewax the floor, use PS87 diluted 1:5.

Coverage: The product, diluted 1:30, covers up to 50mq/l

How to use it

STEP 1
Sweep the floor well.

STEP 2
Dilute CLEANALL 1:30.

STEP 3
Distribute the solution with a floor scrubber fitted with a white pad.

STEP 4
Leave to act for 4-5 minutes and then wash the floor with a brush or floor scrubber fitted with a white pad.

STEP 5
Remove residue with a wet vacuum and rinse with clean water.

STEP 6
Do not walk on the surface until it is completely dry.





surface
care
solutions

Care & Maintenance Sheet

Ceramica Senio S.r.l.

Walls & Tops



surface care solutions

Care & Maintenance Sheet

Ceramica Senio S.r.l.

INITIAL CLEANING

We recommend using DETERDEK for this operation.

The product should be applied after the installation of the tiles to remove superficial residues. DETERDEK is an acid cleaner that can be used on both floor and wall tiles. Do not use on materials that are sensitive to acids.

Coverage: when diluted 1:5, it covers up to 30mq/l



How to use it

<p>STEP 1</p>	<p>STEP 2</p>	<p>STEP 3</p>	<p>STEP 4</p>	<p>STEP 5</p>
<p>Wet the surface with water.</p>	<p>Dilute DETERDEK 1:5</p>	<p>Distribute the solution on the surface with a brush or airless sprayer.</p>	<p>Let sit for 4-5 minutes, then clean the area with an abrasive Scotch Brite sponge or brush.</p>	<p>Remove residue and rinse with clean water.</p>

WATER AND OIL REPELLENT PROTECTION - Water Based

MP90ECO PLUS is recommended for this operation.

Apply the product on the installed and clean material. The sealer reduces the absorption of water and staining agents, without changing the superficial finishing. The product does not protect against acids. Always read the technical data sheets before use. As an alternative, for materials installed outside or in very humid environments, use FOB.

Coverage: It covers up to 10mq/l



How to use it

<p>STEP 1</p>	<p>STEP 2</p>	<p>STEP 3</p>	<p>STEP 4</p>
<p>Clean the surface well.</p>	<p>On a clean and dry surface, apply the product evenly with a brush</p>	<p>Wait 10 minutes, then remove any unabsorbed residue. The product must not form a film.</p>	<p>Do not touch the surface within the first 4 hours and do not wet the surface for 24 hours.</p>



surface care solutions

Care & Maintenance Sheet

Ceramica Senio S.r.l.

WATER AND OIL REPELLENT PROTECTION – Solvent Based

FOB is recommended for this operation.

Apply the product on the installed and clean material. The sealer reduces the absorption of water and staining agents, without changing the superficial finishing. The product does not protect against acids. Always read the technical data sheets before use.

Coverage: It covers up to 10mq/l

How to use it



STEP 1	STEP 2	STEP 3	STEP 4
Clean the surface well.	On a clean and dry surface, apply the product evenly with a brush	Wait 10 minutes, then remove any unabsorbed residue. The product must not form a film.	Do not touch the surface within the first 8 hours and do not wet the surface for 24 hours.

ORDINARY MAINTENANCE

For this operation, we recommend using CLEANALL SPRAY

The product gently but effectively cleans all surfaces without damaging them. It is the ideal product for routine maintenance of surfaces.

How to use it

STEP 1	STEP 2
Spray the product on the surface keeping the bottle upright, 20-30 cm from the point of application.	Clean the area with a soft cloth.





surface
care
solutions

Care & Maintenance Sheet

Ceramica Senio S.r.l.

EXTRAORDINARY MAINTENANCE



For this operation, we recommend CLEANALL.

The product removes stubborn dirt, restoring the floor's original appearance. It is recommended to carry out this cleaning when there is the need. In case of stubborn dirt, use PS87 diluted 1:10. In case of limescale residues, use DETERDEK diluted 1:5.

Coverage: The product, diluted 1:30, covers up to 50mq/l



How to use it

<p>STEP 1</p> 	<p>STEP 2</p> 	<p>STEP 3</p> 	<p>STEP 4</p> 	<p>STEP 5</p> 
<p>Wet the surface with water.</p>	<p>Dilute CLEANALL 1:30</p>	<p>Distribute the solution on the surface with a brush or airless sprayer.</p>	<p>Let sit for 4-5 minutes, then clean the area with an abrasive Scotch Brite sponge or brush.</p>	<p>Remove residue and rinse with clean water.</p>



surface
care
solutions

Care & Maintenance Sheet

Ceramica Senio S.r.l.

STAIN CHART

OIL AND GREASE	NOSPOT
CARBONATED BEVERAGES AND JUICES	SR95
URINE AND VOMIT	
COFFEE AND WINE	
BLOOD	
INK / MARKER	
NICOTINE	
HAIR DYE	
SILICONE	
POLYURETHANE FOAM	
ADHESIVE TAPE RESIDUE	
RESIN	
RUST	NORUST

NOTE

Avoid the use of acidic or alkaline substances, or solvent-based cleaning agents for the ordinary maintenance.

In case of special situations, contact FILA to evaluate further solutions.

For any enquiries, please write to info@filasolutions.com.